



HITACHI COMPACT EXCAVATOR ATTACHMENTS

It's time to maximize productivity and experience true versatility with Viking West Hitachi Compact Excavator Attachments. Our Heavy Duty Dig Buckets, Clean-up Buckets, and Direct Link Thumbs will take your machine from average to advanced. Delivering dependable and outstanding performance, these attachments are must-haves for excavator operators in any industry.



ZX17 THRU ZX60 HD ATTACHMENTS

KEY FEATURES



TESTING AND STRESS ANALYSIS



ENGINEERED WELDING



HIGH-STRENGTH ABRASION-RESISTANT STEEL



HIGH-PRESSURE CYLINDERS



INDUCTION-HARDENED BUSHINGS



AR500 BOLT-ON CUTTING EDGE



MAXIMUM PRODUCTIVITY



EVERY VIKING WEST COMPACT EXCAVATOR ATTACHMENT COMES WITH AN INDUSTRY-LEADING 24-MONTH WARRANTY.





SPECIFICATIONS

HEAVY DUTY DIG BUCKET

The specifications for the Heavy Duty Dig Bucket are as follows:

WEDGE LOCK LUGGING

SERIES	WIDTH (in)	SKU	WEIGHT (kg/lb)	CAPACITY (m ³ /yd ³)	LUGGING STYLE	TOOTH SERIES	TOOTH CLASS	TOOTH STYLE	# OF TEETH
ZX17	12"	101886	64/141	0.02/0.03	Hitachi Wedge Lock	Cat J	J200	Standard Long	3
ZX17	18"	101555	64/141	0.04/0.05	Hitachi Wedge Lock	Cat J	J200	Standard Long	4
ZX25/ZX30/ZX35	12"	100226	67/148	0.05/0.07	Hitachi Wedge Lock	Cat J	J200	Standard Long	3
ZX25/ZX30/ZX35	18"	100229	85/186	0.08/0.10	Hitachi Wedge Lock	Cat J	J200	Standard Long	4
ZX25/ZX30/ZX35	24"	100231	98/216	0.11/0.14	Hitachi Wedge Lock	Cat J	J200	Standard Long	4
ZX50	12"	100237	97/213	0.08/0.10	Hitachi Wedge Lock	Cat J	J200	Standard Long	3
ZX50	18"	100240	118/260	0.12/0.16	Hitachi Wedge Lock	Cat J	J200	Standard Long	4
ZX50	24"	100242	137/302	0.17/0.23	Hitachi Wedge Lock	Cat J	J200	Standard Long	4
ZX60	12"	100480	100/220	0.08/0.10	Hitachi Wedge Lock	Cat J	J200	Standard Long	3
ZX60	18"	100483	120/265	0.12/0.16	Hitachi Wedge Lock	Cat J	J200	Standard Long	4
ZX60	24"	100485	140/307	0.17/0.23	Hitachi Wedge Lock	Cat J	J200	Standard Long	4

HEAVY DUTY CLEAN-UP BUCKET

The specifications for the Heavy Duty Clean-up Bucket are as follows:

WEDGE LOCK LUGGING

SERIES	WIDTH (in)	SKU	WEIGHT (kg/lb)	CAPACITY (m ³ /yd ³)	LUGGING STYLE	CUTTING EDGE	CUTTING EDGE THICKNESS (mm/in)
ZX17	24"	101659	72.1/144.2	0.05/0.07	Hitachi Wedge Lock	1pc Double Bevel Flat	16/0.63
ZX17	30"	101891	86.6/190.4	0.07/0.09	Hitachi Wedge Lock	1pc Double Bevel Flat	16/0.63
ZX25/ZX30/ZX35	30"	100233	123.0/270.6	0.14/0.18	Hitachi Wedge Lock	1pc Double Bevel Flat	16/0.63
ZX25/ZX30/ZX35	36"	100235	141.5/311.3	0.16/0.21	Hitachi Wedge Lock	1pc Double Bevel Flat	16/0.63
ZX50	36"	100244	175.9/387.0	0.26/0.34	Hitachi Wedge Lock	1pc Double Bevel Flat	16/0.63
ZX50	42"	100246	204.9/450.8	0.35/0.46	Hitachi Wedge Lock	1pc Double Bevel Flat	16/0.63
ZX60	36"	100487	175.9/387.0	0.26/0.34	Hitachi Wedge Lock	1pc Double Bevel Flat	16/0.63
ZX60	42"	100489	204.9/450.8	0.35/0.46	Hitachi Wedge Lock	1pc Double Bevel Flat	16/0.63

HEAVY DUTY DIRECT LINK THUMB

The specifications for the Heavy Duty Direct Link Thumb are as follows:

WEDGE LOCK QUICK CHANGE

SERIES	SKU	WIDTH (mm/in)	LENGTH (mm/in)	WEIGHT WITH CYLINDER (kg/lb)	CYLINDER PIN DIAMETER (mm/in)	PIVOT PIN DIAMETER	# OF TINES	CYLINDER PORT SIZE	TAIL MOUNT INCLUDED	REPLACEABLE BUSHINGS	HARD-SURFACING ON TINES
ZX17	101574	330/13.0	645/25.4	38.7/85.1	20/0.8	30/1.2	2	ORB-4	No	Yes	No
ZX25	101832	386/15.2	760/29.9	54.9/120.8	25/1.0	35/1.4	2	ORB-4	No	Yes	No
ZX30/ZX35	100257	386/15.2	760/29.9	54.9/120.8	25/1.0	35/1.4	2	ORB-4	No	Yes	No
ZX50/ZX60	100261	420/16.5	930/36.6	71.9/158.2	25/1.0	45/1.8	2	ORB-4	No	Yes	No